


Datasheet Conveyor Belt

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 RZF
- **Nitta Japan code:**
CC-16DKC3



Construction:	2 plies polyester/viscose, rigid
----------------------	----------------------------------

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	Fabric	PVC	Fabric	
Thickness:	-		-	mm (approx.)
Colour:	-	White	-	
Hardness:	-		-	
Profile:	-		-	

Total thickness:	2,6	mm (approx.)
Weight:	2,3	kg/m ² (approx.)
Max. width:	2100	mm
Belt support:	Sliderbed (Rollers), Flat	

Rating at 1% elongation:	12	N/mm
Advised pretension:	2 - 7	N/mm
Maximum allowable tension:	22	N/mm
Temperature range:	-10 to +90	°C

Minimum pulley diameters:		
Flexing:	20	mm
Backflexing:	20	mm

Special approval:	FDA, 10/2011/EC + amendments
--------------------------	------------------------------

Applications:	<ul style="list-style-type: none"> Conveyor belt in bakeries Excellent release of dough in bakeries Conveying of (un)vulcanised rubber Proofer cabinets
----------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------